



Test Report No.: FS180817N043



TEST REPORT



Applicant	Particle Industries, Inc
Address	126 Post St,4th floor, San Francisco, CA 94108 USA

Manufacturer or Supplier	Particle Industries, Inc
Address	126 Post St,4th floor, San Francisco, CA 94108 USA
Product	Argon
Brand Name	Particle Industries, Inc
Model	ARGN
Additional Model & Model Difference	N/A
Date of tests	Aug. 17, 2018 ~ Oct. 25, 2018

The submitted sample of the above equipment has been tested for according to the requirements of the following standards:

- FCC Part 15, Subpart B, Class B (sDoC)
- ICES-003 Issue 6:2016, Class B

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Breeze Jiang Project Engineer / EMC Department	Approved by Madison Luo Supervisor / EMC Department
	 Date: Dec. 03, 2018

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

RELEASE CONTROL RECORD	3
1 SUMMARY OF TEST RESULTS	4
1.1 MEASUREMENT UNCERTAINTY	4
2 GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
2.2 DESCRIPTION OF TEST MODES	6
2.3 DESCRIPTION OF SUPPORT UNITS	6
2.4 CONFIGURATION OF SYSTEM UNDER TEST	7
3 EMISSION TEST	8
3.1 CONDUCTED EMISSION MEASUREMENT	8
3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	8
3.1.2 TEST INSTRUMENTS	8
3.1.3 TEST PROCEDURE	9
3.1.4 DEVIATION FROM TEST STANDARD	9
3.1.5 TEST SETUP	10
3.1.6 EUT OPERATING CONDITIONS	10
3.1.7 TEST RESULTS	11
3.2 RADIATED EMISSION MEASUREMENT	13
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	13
3.2.2 TEST INSTRUMENTS	15
3.2.3 TEST PROCEDURE	16
3.2.4 DEVIATION FROM TEST STANDARD	16
3.2.5 TEST SETUP	18
3.2.6 EUT OPERATING CONDITIONS	19
3.2.7 TEST RESULTS	20
4 PHOTOGRAPHS OF THE TEST CONFIGURATION	25
5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	28



BUREAU
VERITAS

Test Report No.: FS180817N043

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FS180817N043	Original release	Dec. 03, 2018

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD			
Standard Section	Test Item	Result	Remark
FCC Part 15 Subpart B, Class B (sDoC) ICES-003 Issue 6: 2016, Class B	Conducted emission test	PASS	Meets limits minimum passing margin is -30.77 dB at 0.74621 MHz
	Radiated Emission Test (9KHz ~ 1GHz)	PASS	Meets limits minimum passing margin is -12.85 dB at 39.604 MHz
	Radiated Emission Test Above 1GHz	PASS	Meets limits minimum passing margin is -15.10 dB at 6834.540MHz

Remark: Please refer to FCC part 2 2.1077 for sDoC compliance information requirement

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emission test	0.15MHz ~ 30MHz	+/- 2.70 dB
Radiated emissions test	9kHz-30MHz	+/- 2.90 dB
	30MHz ~1GHz	+/- 4.04 dB
	1GHz ~ 6GHz	+/- 5.02 dB



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Argon
MODEL NO.	ARGN
ADDITIONAL MODEL	N/A
POWER SUPPLY	Li+ PIN /Battery connector: DC 3.7V from Li-ion Battery or VUSB PIN /USB connector :DC 5V from USB Host Unit
CABLE SUPPLIED	N/A
THE HIGHEST OPERATING FREQUENCY	2480MHz

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was showed in test report.
3. Please refer to the EUT photo document (Reference No.: 180817N043) for detailed product photo.
4. The EUT is wireless module, it no any accessories, the test standard were specified by applicant.



2.2 DESCRIPTION OF TEST MODES

The EUT were tested under the following modes, the final worst mode was marked in boldface and recorded in this report

◆ **FOR CONDUCTED EMISSIONS TEST:**

Test Mode	Test Voltage
2.4G Wireless Normal Working	DC5V from Adapter
NFC Normal Working	
WIFI Link Data Transmtting	

◆ **FOR RADIATED EMISSIONS TEST(Below 30MHz):**

Test Mode	Test Voltage
NFC Normal Working	DC 3.7V from Battery
	DC5V from Adapter

◆ **FOR RADIATED EMISSIONS TEST(Below 1GHz):**

Test Mode	Test Voltage
2.4G Wireless Normal Working	DC 3.7V from Battery
NFC Normal Working	
WIFI Link Data Transmtting	
2.4G Wireless Normal Working	DC5V from Adapter
WIFI Link Data Transmtting	
NFC Normal Working	

◆ **FOR RADIATED EMISSIONS TEST(Above 1GHz):**

Test Mode	Test Voltage
2.4G Wireless Normal Working	DC 3.7V from Battery
WIFI Link Data Transmtting	



2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Adapter	N/A	DC 5V 1.5A	N/A	N/A
2	iPhone 6s	Apple	ML7F2CH/A	C6KQKXLAGRY8	N/A
3	Li-ion Battery	N/A	DC3.7V	N/A	N/A

NO.	DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	USB Line: Unshielded detachable 0.6m.
2, 3	N/A



3 EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.107)

ICES-003 (Class A: section 6.1) (Class B: section 6.1)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

- NOTES:**
- (1) The lower limit shall apply at the transition frequencies.
 - (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 - (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101494	Apr. 05,18	Apr. 04,19
Artificial Mains Network	Rohde&Schwarz	ENV216	101173	Mar. 03,18	Mar. 02,19
Artificial Mains Network	Rohde&Schwarz	ESH3-Z5	100317	Apr. 05,18	Apr. 04,19
Voltage probe	SCHWARZBECK	TK 9421	TK 9421-176	Jan. 17,18	Jan. 16,19
Test software	ADT	ADT_Conc _V7.3.7	N/A	N/A	N/A

- NOTE:**
- 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 - 2. The test was performed in shielding room 553.

3.1.3 TEST PROCEDURE

The basic test procedure was in accordance with ANSI C63.4:2014 (section 7).

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20dB) were not recorded.

NOTE:


1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.



3.1.5 TEST SETUP



- Note:**
- 1.Support units were connected to second LISN.
 - 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.

3.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power of all equipment.
- b. EUT was operated according to the type description in manufacturer's specifications or the User's Manual.




3.1.7 TEST RESULTS

TEST MODE	2.4G Wireless Normal Working	6DB BANDWIDTH	9 kHz
TEST VOLTAGE	DC 5V from Adapter	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	22deg. C, 46% RH	TESTED BY	Dragon

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15924	9.78	10.16	0.36	19.94	10.14	65.50	55.50	-45.56	-45.36
2	0.74621	10.14	8.44	5.09	18.58	15.23	56.00	46.00	-37.42	-30.77
3	1.45275	10.22	1.83	-5.98	12.05	4.24	56.00	46.00	-43.95	-41.76
4	2.58450	9.94	3.11	-2.50	13.05	7.44	56.00	46.00	-42.95	-38.56
5	4.30125	9.95	9.36	-0.34	19.31	9.61	56.00	46.00	-36.69	-36.39
6	15.06300	9.78	8.77	5.09	18.55	14.87	60.00	50.00	-41.45	-35.13


REMARKS: The emission levels of other frequencies were very low against the limit.



TEST MODE	2.4G Wireless Normal Working	6DB BANDWIDTH	9 kHz
TEST VOLTAGE	DC 5V from Adapter	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	22deg. C, 46% RH	TESTED BY	Dragon

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15225	9.72	17.69	2.55	27.41	12.27	65.88	55.88	-38.47	-43.61
2	0.17651	10.22	14.70	1.89	24.92	12.11	64.65	54.65	-39.73	-42.54
3	0.75525	9.98	12.79	3.20	22.77	13.18	56.00	46.00	-33.23	-32.82
4	1.12653	9.70	3.96	-1.66	13.66	8.04	56.00	46.00	-42.34	-37.96
5	2.06475	10.23	-0.17	-4.26	10.06	5.97	56.00	46.00	-45.94	-40.03
6	4.62300	9.74	6.77	-0.98	16.51	8.76	56.00	46.00	-39.49	-37.24

REMARKS: The emission levels of other frequencies were very low against the limit.





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15 (Section: 15.209)

ICES-003 for below 1GHz (Class A: section 6.2.1 Table 4; Class B: section 6.2.1 Table 5); for above 1GHz (Class A: section 6.2.2 Table 6; Class B: section 6.2.2 Table 7)

Radiated Emissions Limits at 3 meters (dBµV/m)	
Frequencies (MHz)	FCC 15
0.009-0.490	128.5-93.8
0.490-1.705	73.8-62.97
1.705-30.0	69.50

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.109)

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 10 meters (dBµV/m)				
Frequencies (MHz)	FCC 15B/ ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	39	29.5	40	30
88-216	43.5	33.1		
216-230	46.4	35.6		
230-960			47	37
960-1000	49.5	43.5		

Radiated Emissions Limits at 3 meters (dBµV/m)				
Frequencies (MHz)	FCC 15B / ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	49.5	40	50	40
88-216	54	43.5		
216-230	56.9	46		
230-960			57	47
960-1000	60	54		
1000-3000	Avg: 60 Peak: 80	Avg: 54 Peak: 74	Avg: 56 Peak: 76	Avg: 50 Peak: 70
Above 3000			Avg: 60 Peak: 80	Avg: 54 Peak: 74



FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower

- Note: (1) The lower limit shall apply at the transition frequencies.
(2) Emission level (dBuV/m) = 20 log Emission level (uV/m).
(3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.



3.2.2 TEST INSTRUMENTS

FOR FREQUENCY 9KHz-30MHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101564	Jan. 18,18	Jan. 17,19
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	1519B-045	May 31,18	May 30,19
Amplifier	Burgeon	BPA-530	100210	Apr. 05,18	Apr. 04,19
Test Software	ADT	ADT_Radiated_V8.7.07	N/A	N/A	N/A

- NOTES:** 1. The test was performed in 10m Chamber.
 2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 3. The FCC Site Registration No. is 749762.

FOR FREQUENCY 30MHz-1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU26	100005	Jun. 05,18	Jun. 04,19
EMI Test Receiver	Rohde&Schwarz	ESR7	101564	Jan. 18,18	Jan. 17,19
Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	9168-555	Nov. 10, 18	Nov. 09, 19
Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	9168-554	Dec. 10, 17	Dec. 09, 18
Preamplifier	EMCI	EMC1135	980378	Mar. 20,18	Mar. 19,19
Preamplifier	EMCI	EMC1135	980423	Mar. 20,18	Mar. 19,19
10m Semi-anechoic Chamber	CHANGLING	21.4m*12.1m*8.8m	NSEMC006	Feb. 10,18	Feb. 09,19
Test Software	ADT	ADT_Radiated_V8.7.07	N/A	N/A	N/A

- NOTES:** 1. The test was performed in 10m Chamber.
 2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 3. The FCC Site Registration No. is 749762.

FREQUENCY RANGE ABOVE 1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Horn Antenna	ETS-Lindgren	3117	00085519	Dec. 10, 17	Dec. 09, 18
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170242	May 05,18	May 04,19
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV40	101003	Apr. 21,18	Apr. 20,19
Broadband Preamplifier (1~18GHz)	SCHWARZBECK	BBV9718	266	Apr. 18,18	Apr. 18,19
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 08,17	Nov. 07,18
Test Software	ADT	ADT_Radiated_V8.7.07	N/A	N/A	N/A

- NOTES:** 1. The test was performed in 10m Chamber.
 2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 3. The FCC Site Registration No. is 749762.

3.2.3 TEST PROCEDURE

FOR FREQUENCY 9KHZ-30MHZ

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meters Semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was fixed of loop antenna
- c. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 30MHz.

FOR FREQUENCY 30MHz-1GHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.

NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
3. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
4. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB) (if the raw value contains the amplifier).
5. Margin value = Emission level – Limit value.

<Frequency Range above 1GHz>

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meters Semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.

NOTE:

1. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz for Average detection (AV) at frequency above 1GHz.
2. For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the receiver antenna.
3. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
4. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
5. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB) (if the raw value contains the amplifier)
6. Margin value = Emission level – Limit value.


3.2.4 DEVIATION FROM TEST STANDARD

No deviation.




3.2.5 TEST SETUP


<Frequency Range 9KHz-30MHz>



<Frequency Range 30MHz - 1GHz>



<Frequency Range above 1GHz>



* depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3

3.2.6 EUT OPERATING CONDITIONS

- Turn on the power supply of the EUT.
- EUT was operated according to the type description in manufacturer's specifications or the User's Manual.




3.2.7 TEST RESULTS

TEST MODE	NFC Normal Working	FREQUENCY RANGE	9 KHz -30MHz
TEST VOLTAGE	DC 5V from Adapter	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 200Hz
ENVIRONMENTAL CONDITIONS	21deg. C, 67% RH	TESTED BY: Ming Bai	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M								
No	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	0.0090	-10.64	61.50	50.86	128.52	-77.66	100	195
2	2.2734	-10.91	38.26	27.35	69.54	-42.19	100	150
3	4.4644	-10.68	39.35	28.67	69.54	-40.87	100	171
4	10.1975	-10.54	39.36	28.82	69.54	-40.72	100	162
5	14.9303	-10.82	38.96	28.14	69.54	-41.40	100	171
6	19.9390	-10.08	37.77	27.69	69.54	-41.85	100	178


- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
 2. Negative sign (-) in the margin column signify levels below the limit.
 3. Frequency range scanned: 0.009-0.15MHz.
 4. Only emissions significantly above equipment noise floor are reported.



TEST MODE	NFC Normal Working	FREQUENCY RANGE	9 KHz -30MHz
TEST VOLTAGE	DC 5V from Adapter	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 200Hz
ENVIRONMENTAL CONDITIONS	21deg. C, 67% RH	TESTED BY: Ming Bai	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M								
No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	0.0090	-10.64	62.14	51.50	128.52	-77.02	100	239
2	2.7428	-10.80	39.43	28.63	69.54	-40.91	100	246
3	6.7183	-10.69	40.12	29.43	69.54	-40.11	100	110
4	11.2667	-10.61	39.45	28.84	69.54	-40.70	100	112
5	15.7311	-10.71	38.48	27.77	69.54	-41.77	100	110
6	21.5766	-10.10	38.04	27.94	69.54	-41.60	100	115


- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
 2. Negative sign (-) in the margin column signify levels below the limit.
 3. Frequency range scanned: 0.009-0.15MHz.
 4. Only emissions significantly above equipment noise floor are reported.



TEST MODE	WIFI Link data transmitting	FREQUENCY RANGE	30-1000MHz
TEST VOLTAGE	DC 3.7V from Battery	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120kHz
ENVIRONMENTAL CONDITIONS	21.0deg. C, 59.0% RH	TESTED BY: Luke	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 10 M								
No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	46.854	-17.30	31.59	14.29	30.00	-15.71	400	53
2	226.304	-18.22	35.12	16.90	30.00	-13.10	200	210
3	249.463	-17.42	35.63	18.21	37.00	-18.79	400	43
4	369.136	-13.97	33.15	19.18	37.00	-17.82	200	252
5	380.898	-13.81	32.64	18.83	37.00	-18.17	200	162
6	475.836	-11.74	33.82	22.08	37.00	-14.92	200	35


- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
 2. Negative sign (-) in the margin column signify levels below the limit.
 3. Frequency range scanned: 30MHz to 1000MHz.
 4. Only emissions significantly above equipment noise floor are reported.



TEST MODE	WIFI Link data transmitting	FREQUENCY RANGE	30-1000MHz
TEST VOLTAGE	DC 3.7V from Battery	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120kHz
ENVIRONMENTAL CONDITIONS	21.0deg. C, 59.0% RH	TESTED BY: Luke	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 10 M								
No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	39.604	-17.77	34.92	17.15	30.00	-12.85	100	211
2	159.841	-15.98	30.61	14.63	30.00	-15.37	100	210
3	237.881	-16.70	33.41	16.71	37.00	-20.29	100	302
4	251.899	-16.18	33.01	16.83	37.00	-20.17	300	12
5	353.851	-12.93	33.28	20.35	37.00	-16.65	100	269
6	475.786	-10.50	31.26	20.76	37.00	-16.24	300	357

- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
 2. Negative sign (-) in the margin column signify levels below the limit.
 3. Frequency range scanned: 30MHz to 1000MHz.
 4. Only emissions significantly above equipment noise floor are reported.



ABOVE 1GHz



TEST MODE	2.4G Wireless Normal Working	FREQUENCY RANGE	Above 1GHz
TEST VOLTAGE	DC 3.7V from Battery	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Peak, Average 1MHz
ENVIRONMENTAL CONDITIONS	21.0deg. C, 59.0% RH	TESTED BY: Daniel	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	6834.540PK	12.59	45.01	57.60	74.00	-16.40	100	156
2	6834.540AV	12.59	26.31	38.90	54.00	-15.10	100	156
3	9763.450PK	16.55	41.75	58.30	74.00	-15.70	100	58
4	9763.450AV	16.55	22.15	38.70	54.00	-15.30	100	58
5	15167.350PK	26.12	31.68	57.80	74.00	-16.20	100	254
6	15167.350AV	26.12	12.28	38.40	54.00	-15.60	100	254
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	6975.350PK	13.07	45.53	58.60	74.00	-15.40	100	124
2	6975.350AV	13.07	25.63	38.70	54.00	-15.30	100	124
3	10056.870PK	16.86	41.04	57.90	74.00	-16.10	100	58
4	10056.870AV	16.86	21.54	38.40	54.00	-15.60	100	58
5	15673.450PK	27.04	31.56	58.60	74.00	-15.40	100	97
6	15673.450AV	27.04	11.76	38.80	54.00	-15.20	100	97


- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
 2. Negative sign (-) in the margin column signify levels below the limit.
 3. Frequency range scanned: 1GHz to 18GHz.
 4. Only emissions significantly above equipment noise floor are reported.

4 PHOTOGRAPHS OF THE TEST CONFIGURATION


CONDUCTED EMISSION TEST




RADIATED EMISSION TEST (9KHz - 30MHz)



RADIATED EMISSION TEST (30MHz-1GHz)



RADIATED EMISSION TEST (ABOVE 1GHz)





**BUREAU
VERITAS**

Test Report No.: FS180817N043

5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---