


TEST REPORT



Applicant	Particle Industries, Inc
Address	126 Post St, 4th floor, San Francisco, CA 94108 USA

Manufacturer or Supplier	Particle Industries, Inc	
Address	126 Post St, 4th floor, San Francisco, CA 94108 USA	
Product	B SOM	
Brand Name	Particle Industries, Inc	
Model	B520	
Additional Model & Model Difference	B523, see section 2.2 note	
Date of tests	Jan. 04, 2020 ~ Apr. 17, 2020	

The submitted sample of the above equipment has been tested according to the requirements of the following standards:

- EN 55032:2015, Class B
- EN 55035:2017
- EN 301 489-1 V2.2.3 (2019-11)
- EN 301 489-3 V2.1.1 (2019-03)
- Draft EN 301 489-17 V3.2.2(2019-12)

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Breeze Jiang Project Engineer / EMC Department	Approved by Madison Luo Assistant Manager / EMC Department
	
	Date: May 19, 2020

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



Table of Contents

1	SUMMARY OF TEST RESULTS	4
1.1	MEASUREMENT UNCERTAINTY	5
2	GENERAL INFORMATION	6
2.1	GENERAL DESCRIPTION OF EUT	6
2.2	DESCRIPTION OF TEST MODES	7
2.3	TEST PROGRAM USED AND OPERATION DESCRIPTIONS	8
2.4	MISCELLANEOUS	8
2.5	GENERAL DESCRIPTION OF APPLIED STANDARDS	9
2.6	DESCRIPTION OF SUPPORT UNITS	9
3	RADIATED EMISSION MEASUREMENT	10
3.1	LIMITS OF RADIATED EMISSION MEASUREMENT	10
3.2	TEST INSTRUMENTS	12
3.3	TEST PROCEDURE	13
3.4	TEST SETUP	15
3.5	SUPPLEMENTARY INFORMATION	15
3.6	TEST RESULTS (BELOW 1GHZ)	16
3.7	TEST RESULTS (ABOVE 1GHZ)	18
4	IMMUNITY TEST	19
4.1	GENERAL DESCRIPTION	19
4.1.1	GENERAL DESCRIPTION OF EN 55035	19
4.1.2	PERFORMANCE CRITERIA	20
4.1.3	EUT OPERATING CONDITION	21
4.2	ELECTROSTATIC DISCHARGE IMMUNITY TEST (ESD) (EN55035, EN301489)	22
4.2.1	TEST SPECIFICATION	22
4.2.2	TEST INSTRUMENTS	22
4.2.3	TEST PROCEDURE	23
4.2.4	DEVIATION FROM TEST STANDARD	24
4.2.5	TEST SETUP	24
4.2.6	TEST RESULTS	25
4.3	RADIATED, RADIO-FREQUENCY, ELECTROMAGNETIC FIELD IMMUNITY TEST (RS) (EN55035)	27
4.3.1	TEST SPECIFICATION	27
4.3.2	TEST INSTRUMENTS	27
4.3.3	TEST PROCEDURE	28
4.3.4	DEVIATION FROM TEST STANDARD	28
4.3.5	TEST SETUP	29
4.3.6	TEST RESULTS	31
4.4	RADIATED, RADIO-FREQUENCY, ELECTROMAGNETIC FIELD IMMUNITY TEST (RS) (EN301489)	32
4.4.1	TEST SPECIFICATION	32
4.4.2	TEST INSTRUMENT	32
4.4.3	TEST PROCEDURE	33
4.4.4	DEVIATION FROM TEST STANDARD	33
4.4.5	TEST SETUP	33
4.4.6	TEST RESULTS	34
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	35
6	APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	37



**BUREAU
VERITAS**

Test Report No.: CE191231N001

RELEASE CONTROL RECORD

Issue No.	Description	Date Issued
CE191231N001	Original release	May 19, 2020



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

EMISSION			
Standard	Test Item	Result	Remark
EN 55032:2015, Class B	Radiated emission 30MHz-1000MHz	PASS	Minimum passing margin is -10.17dB at 847.9934MHz
	Radiated emission 1GHz -6GHz	PASS	Minimum passing margin is -8.79dB at 2156.37MHz.

Note: EN55032:2015 version is required by client and it will also remark in report that it comply with previous standard EN 55032:2012 + AC:2013.

IMMUNITY (EN 55035:2017)			
Standard	Test Type	Result	Remark
IEC 61000-4-2: 2008 ED. 2.0	Electrostatic discharge immunity test	PASS	Electrostatic Discharge – ESD: 8kV Air discharge, 4kV Contact discharge, Performance Criterion A
IEC 61000-4-3: 2010 ED. 3.2	Radiated, radio-frequency, electromagnetic field immunity test	PASS	Radio-Frequency Electromagnetic Field Susceptibility Test – RS: 80-1000 MHz, 3V/m, 80% AM (1kHz), 1800 MHz,3V/m, 80% AM (1kHz), 2600 MHz,3V/m, 80% AM (1kHz), 3500 MHz,3V/m, 80% AM (1kHz), 5000 MHz,3V/m, 80% AM (1kHz) Performance Criterion A

IMMUNITY (EN 301 489-1 V2.2.3, EN 301 489-3 V2.1.1, Draft EN 301489-17 V3.2.2)			
Standard	Test Type	Result	Remark
EN 61000-4-2:2009	Electrostatic discharge immunity test	PASS	Electrostatic Discharge – ESD: 8kV Air discharge, 4kV Contact discharge, Performance Criterion A
EN 61000-4-3:2006 A1:2008 + A2:2010	Radiated, radio-frequency, electromagnetic field immunity test	PASS	Radio-Frequency Electromagnetic Field Susceptibility Test – RS: 80-6000 MHz, 3V/m, 80% AM (1kHz), Performance Criterion A



1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

MEASUREMENT	FREQUENCY	UNCERTAINTY
Radiated Disturbance Test	30MHz ~ 1000MHz	+/- 3.99 dB
	1GHz ~ 6GHz	+/- 4.62 dB



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	B SOM
BRAND	Particle Industries,Inc
TEST MODEL	B520
ADDITIONAL MODEL	B523
POWER SUPPLY	3V3 : DC +3.3V (2.8-3.6V), VCC: 3.8V (DC+3.3-4.3V)
CABLE SUPPLIED	N/A
THE HIGHEST OPERATING FREQUENCY	2.48GHz

Note:

1. For the test results, the EUT had been tested with all conditions. But only the worst case was showed in test report.
2. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
3. Please refer to the EUT photo document (Reference No.: 191231N001) for detailed product photo.
4. The EUT is wireless module, it no any accessories, the test standard and items were specified by applicant.



2.2 DESCRIPTION OF TEST MODES

The EUT were tested under the following modes, the final worst mode was marked in boldface and recorded in this report.

◆ **FOR RADIATED EMISSIONS TEST(Below 1GHz):**

Test Mode	Test Voltage
BT Normal Working	DC 3.3V and DC3.8V from Som test board V05A
NFC Normal Working	

◆ **FOR RADIATED EMISSIONS TEST(Above 1GHz):**

Test Mode	Test Voltage
BT Normal Working	DC 3.3V and DC3.8V from Som test board V05A

◆ **FOR ESD AND RS IMMUNITY TEST**

Test Mode	Test Voltage
BT Normal Working	DC 3.3V and DC3.8V from Som test board V05A
NFC Normal Working	

Remarks: The Som test board V05A is support units, it power by 3.8V battery.




2.3 TEST PROGRAM USED AND OPERATION DESCRIPTIONS

- a. Turn on the power supply of the EUT.
- b. EUT was operated according to the type description in manufacturer's specifications or the User's Manual.

2.4 MISCELLANEOUS

➤ Affix CE marking

The marking must be placed visibly and legibly on the product or, if not possible due to the nature of the product, be affixed to the packaging and the accompanying document. The CE marking shall consist of the initials 'CE' taking the following form:



The various components of the CE marking must have the same vertical dimension, and may not be smaller than 5 mm. If the CE marking is reduced or enlarged, the proportions given in the graduated drawing above must be respected.

When the product is subject to other Directives covering other aspects and which also provide for the 'CE' marking, the accompanying documents must indicate that the product also conforms to those other Directives.

However, when one or more of those Directives allow the manufacturer, during a transitional period, to choose which arrangements to apply, the 'CE' marking has to indicate conformity only with the Directives applied by the manufacturer. In this case, the particularities of the Directives applied, as published in the Official Journal of the European Union, must be given in the documents, notices or instructions required by the Directives and accompanying such products.



2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to the specifications of the manufacturers, the EUT must comply with the requirements of the following standards:

EN 55032:2015, CLASS B

EN 55035:2017

IEC 61000-4-2:2008 ED. 2.0

IEC 61000-4-3:2010 ED. 3.2

EN 301 489-1 V2.2.3 (2019-11)

EN 301 489-3 V2.1.1 (2019-03)

DRAFT EN 301 489-17 V3.2.2(2019-12)

EN 61000-4-2:2009

EN 61000-4-3:2006 + A1:2008 + A2:2010

All applicable tests have been performed and recorded as per the above standards.

The EUT haven't any components susceptible to magnetic fields, so don't test power-frequency magnetic filed item.

2.6 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	iPhone 6s	Apple	ML7F2CH/A	C6KQKXLAGRY8	N/A
2	Li-ion Battery	N/A	DC3.8V	N/A	N/A
3	SOM test Board	Particle	V05A	38069A-403-191206	N/A
4	Mobile Phone	Apple	MQA52CH/A	F2LW4YY9JCLF	N/A

NO.	DESCRIPTION OF THE ABOVE SUPPORT UNITS
1~4	N/A



3 RADIATED EMISSION MEASUREMENT

3.1 LIMITS OF RADIATED EMISSION MEASUREMENT

FOR FREQUENCY BELOW 1000 MHz

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 10m)
	Quasi-Peak dBuV/m	Quasi-Peak dBuV/m
30 – 230	40	30
230 – 1000	47	37

FREQUENCY (MHz)	Class A (at 3m)	Class B (at 3m)
	Quasi-Peak dBuV/m	Quasi-Peak dBuV/m
30 – 230	50	40
230 – 1000	57	47

For FM receivers

Distance (m)	Source	Frequency Range (MHz)	Limits dB (uV/m)	
			Quasi-peak	
10	Local oscillator	≤1000	Fundamental	50
		30 to 300	Harmonics	42
		300 to 1000	Harmonics	46
	Other	30 to 230		30
230 to 1000			37	
3	Local oscillator	≤1000	Fundamental	60
		30 to 300	Harmonics	52
		300 to 1000	Harmonics	56
	Other	30 to 230		40
		230 to 1000		47



FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	Up to 5 times of the highest frequency or 6 GHz, whichever is less

FOR FREQUENCY ABOVE 1000 MHz

FREQUENCY (GHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
1 to 3	76	56	70	50
3 to 6	80	60	74	54

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
 3. All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.



3.2 TEST INSTRUMENTS

FREQUENCY RANGE BELOW 1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU26	100005	May 20,19	May 19, 20
EMI Test Receiver	Rohde&Schwarz	ESR7	101564	Mar. 18,20	Mar. 17,21
Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	9168-555	Nov. 24, 19	Nov. 23, 20
Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	9168-554	Dec. 01, 19	Nov. 30, 20
Preamplifier	EMCI	EMC1135	980378	Mar. 15,20	Mar. 14,21
Preamplifier	EMCI	EMC1135	980423	Mar. 15,20	Mar. 14,21
10m Semi-anechoic Chamber	CHANGLING	21.4m*12.1m* 8.8m	NSEMC006	Oct. 19,19	Oct. 18,20
Test Software	ADT	ADT_Radiated_V8.7.07	N/A	N/A	N/A

NOTE: 1. The test was performed in 10m Chamber.

2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

FREQUENCY RANGE ABOVE 1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Horn Antenna	ETS-Lindgren	3117	00085519	Nov. 24, 19	Nov. 23, 20
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170147	Jun. 23,19	Jun. 22,20
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV40	101003	Mar. 18,20	Mar. 17,21
Broadband Preamplifier (1~18GHz)	SCHWARZBECK	BBV9718	266	Apr. 21,19	Apr. 20,20
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Mar. 04,20	Mar. 03,21
Test Software	ADT	ADT_Radiated_V8.7.07	N/A	N/A	N/A

NOTE: 1. The test was performed in 10m Chamber.

2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



3.3 TEST PROCEDURE

<Frequency Range below 1GHz>

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.

NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
3. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
4. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB) (if the raw value contains the amplifier).
5. Margin value = Emission level – Limit value.



<Frequency Range above 1GHz>

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna can be varied from one meter-to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test receiver/spectrum was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.


NOTE:

1. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz for Average detection (AV) at frequency above 1GHz.
2. For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the receiver antenna.
3. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
4. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
5. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB) (if the raw value contains the amplifier).
6. Margin value = Emission level – Limit value.




3.4 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



* : depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3

3.5 SUPPLEMENTARY INFORMATION

The more stringent measurement method of paragraph 8.3.2 in ANSI C63.4:2014 was applied for the test.




3.6 TEST RESULTS (BELOW 1GHz)

TEST MODE	See section 2.2	FREQUENCY RANGE	30-1000MHz
TEST VOLTAGE	See section 2.2	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120kHz
ENVIRONMENTAL CONDITIONS	22.0deg. C, 56.0% RH	TESTED BY: Kamiko	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 10 M								
No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	38.245	-21.05	39.66	18.61	30.00	-11.39	400	43
2	157.9187	-16.21	32.33	16.12	30.00	-13.88	400	11
3	286.9287	-15.02	30.92	15.90	37.00	-21.10	200	156
4	387.5663	-12.31	30.08	17.77	37.00	-19.23	400	184
5	526.155	-8.96	30.42	21.46	37.00	-15.54	400	35
6	614.3038	-6.47	31.71	25.24	37.00	-11.76	400	8

REMARK: The emission levels of other frequencies were very low against the limit.






TEST MODE	See section 2.2	FREQUENCY RANGE	30-1000MHz
TEST VOLTAGE	See section 2.2	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120kHz
ENVIRONMENTAL CONDITIONS	22.0deg. C, 56.0% RH	TESTED BY: Kamiko	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 10 M								
No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	37.7604	-17.53	33.00	15.47	30.00	-14.53	300	115
2	161.0051	-15.55	30.78	15.23	30.00	-14.77	300	358
3	283.7647	-15.63	31.01	15.38	37.00	-21.62	100	125
4	439.8455	-11.19	30.34	19.15	37.00	-17.85	100	328
5	729.9385	-4.83	30.20	25.37	37.00	-11.63	100	294
6	847.9934	-3.81	30.64	26.83	37.00	-10.17	300	18

REMARK: The emission levels of other frequencies were very low against the limit.





3.7 TEST RESULTS (ABOVE 1GHz)

TEST MODE	See section 2.2		
TEST VOLTAGE	See section 2.2	FREQUENCY RANGE	1-6 GHz
ENVIRONMENTAL CONDITIONS	22.0deg. C, 56.0% RH	TESTED BY: Kamiko	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	1165.26PK	-3.01	57.66	54.65	70.00	-15.35	124	160
2	1165.26AV	-3.01	41.58	38.57	50.00	-11.43	124	160
3	1985.69PK	1.53	54.15	55.68	70.00	-14.32	135	209
4	1985.69AV	1.53	38.48	40.01	50.00	-9.99	135	209
5	2156.37PK	2.22	55.62	57.84	70.00	-12.16	136	100
6	2156.37AV	2.22	38.99	41.21	50.00	-8.79	136	100
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	1325.20PK	-2.76	59.01	56.25	70.00	-13.75	154	201
2	1325.20AV	-2.76	41.71	38.95	50.00	-11.05	154	201
3	1985.62PK	1.53	55.99	57.52	70.00	-12.48	163	291
4	1985.62AV	1.53	38.55	40.08	50.00	-9.92	163	291
5	2316.92PK	2.82	54.43	57.25	70.00	-12.75	130	250
6	2316.92AV	2.82	38.28	41.10	50.00	-8.90	130	250

- REMARK:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
 2. Negative sign (-) in the margin column signify levels below the limit.
 3. Frequency range scanned: 1GHz to 6GHz.
 4. Only emissions significantly above equipment noise floor are reported.



4 IMMUNITY TEST

4.1 GENERAL DESCRIPTION

4.1.1 GENERAL DESCRIPTION OF EN 55035

Product Standard	EN 55035:2017	
Basic Standard, specification requirement, and Performance Criteria:	IEC 61000-4-2	Electrostatic Discharge – ESD: 8kV air discharge, 4kV Contact discharge, Performance Criterion B
	IEC 61000-4-3	Radio-Frequency Electromagnetic Field Susceptibility Test – RS: 80-1000 MHz, 3V/m, 80% AM (1kHz), 1800 MHz,3V/m, 80% AM (1kHz), 2600 MHz,3V/m, 80% AM (1kHz), 3500 MHz,3V/m, 80% AM (1kHz), 5000 MHz,3V/m, 80% AM (1kHz) Performance Criterion A

Product Standard	EN 301 489-1 V2.2.3 (2019-11) EN 301 489-3 V2.1.1 (2019-03) Draft EN 301 489-17 V3.2.2(2019-12)	
Basic Standard, Specification, and Performance Criterion required	EN 61000-4-2	Electrostatic Discharge – ESD: 8 kV air discharge, 4 kV contact discharge, Performance Criterion B
	EN 61000-4-3	Radio-Frequency Electromagnetic Field Susceptibility Test – RS: 80 ~ 6000 MHz, 3 V/m, 80% AM (1 kHz), Performance Criterion A



4.1.2 PERFORMANCE CRITERIA

According to Clause 8.2, 8.3, 8.4 of EN 55035:2017 standard, the following describes the general performance criteria.

CRITERION A	The equipment shall continue to operate as intended without operator intervention. No degradation of performance, loss of function or change of operating state is allowed below a performance level specified by the manufacturer when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.
CRITERION B	During the application of the disturbance, degradation of performance is allowed. However, no unintended change of actual operating state or stored data is allowed to persist after the test. After the test, the equipment shall continue to operate as intended without operator intervention; no degradation of performance or loss of function is allowed, below a performance level specified by the manufacturer, when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level (or the permissible performance loss), or recovery time, is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.
CRITERION C	Loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls by the user in accordance with the manufacturer's instructions. A reboot or re-start operation is allowed. Information stored in non-volatile memory, or protected by a battery backup, shall not be lost.

For EN 301 489-3

The phenomena allowed during and after test in each criterion are clearly stated in the following table.

Performance criteria		
Criteria	During test	After test
A	Operate as intended No loss of function No unintentional responses	Operate as intended No loss of function No degradation of performance No loss of stored data or user programmable functions



B	May show loss of function No unintentional responses	Operate as intended Loss of function(s) shall be self-recoverable No degradation of performance No loss of stored data or user programmable functions
---	---	--

The phenomena allowed during and after test in each criterion are clearly stated in the following table.

The Requirement of Performance Criteria		
1	Performance criteria for continuous phenomena applied to transmitters (CT)	Criterion A of the applicable class shall apply
2	Performance criteria for transient phenomena applied to transmitters (TT)	Criterion B of the applicable class shall apply
3	Performance criteria for continuous phenomena applied to receivers (CR)	Criterion A of the applicable class shall apply
4	Performance criteria for transient phenomena applied to receivers (TR)	Criterion B of the applicable class shall apply

Performance criteria		
Criteria	During test	After test
A	Shall operate as intended. (see note). Shall be no loss of function. Shall be no unintentional transmissions.	Shall operate as intended. Shall be no degradation of performance. Shall be no loss of function. Shall be no loss of stored data.
B	May show loss of function	Functions shall be self-recoverable. Shall operate as intended after recovering. Shall be no loss of critical stored data.
C	May be loss of function.	Functions shall be recoverable by the operator. Shall operate as intended after recovering. Shall be no loss of critical stored data.
<p>NOTE: Operate as intended during the test allows a level of degradation in accordance with a and b.</p> <p>(a) For equipment that supports a PER or FER, the minimum performance level shall be a PER or FER less than or equal to 10 %.</p> <p>(b) For equipment that does not support a PER or a FER, the minimum performance level shall be no loss of the wireless transmission function needed for the intended use of the equipment.</p>		

4.1.3 EUT OPERATING CONDITION

Same as item 2.3



4.2 ELECTROSTATIC DISCHARGE IMMUNITY TEST (ESD) (EN55035, EN301489)

4.2.1 TEST SPECIFICATION

Basic Standard:	IEC 61000-4-2
Discharge Impedance:	330 ohm / 150 pF
Discharge Voltage:	Contact Discharge : 4 kV (Direct & Indirect) Air Discharge: 8kV (Direct)
Polarity:	Positive / Negative
Number of Discharge:	20 times at each test point
Discharge Mode:	Single Discharge
Discharge Period:	1-second

4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
ESD Generator	TESEQ	NSG 437	279	Mar. 06,20	Mar. 05,21
Test Software	TESEQ	V03.03	N/A	N/A	N/A
ESD Generator	EM TEST	Dito	V1211112265	Nov. 30,19	Nov. 29,20
Test Software	EM TEST	V 2.31	N/A	N/A	N/A

- NOTE:**
1. The test was performed in ESD Room.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



4.2.3 TEST PROCEDURE

The basic test procedure was in accordance with IEC 61000-4-2:


- a. Electrostatic discharges were applied only to those points and surfaces of the EUT that are accessible to users during normal operation.
- b. The test was performed with at least ten single discharges on the pre-selected points in the most sensitive polarity.
- c. The time interval between two successive single discharges was at least 1 second.
- d. The discharge return cable of the generator shall be kept at a distance of at least 0.2 m from the EUT whilst the discharge is being applied and should not be held by the operator
- e. Contact discharges were applied to the non-insulating coating, with the pointed tip of the generator penetrating the coating and contacting the conducting substrate.
- f. Air discharges were applied with the round discharge tip of the discharge electrode approaching the EUT as fast as possible (without causing mechanical damage) to touch the EUT. After each discharge, the ESD generator was removed from the EUT and re-triggered for a new single discharge. The test was repeated until all discharges were complete.
- g. At least ten single discharges (in the most sensitive polarity) were applied to the Horizontal Coupling Plane at points on each side of the EUT. The ESD generator was positioned horizontally at a distance of 0.1 meters from the EUT with the discharge electrode touching the HCP.
- h. At least ten single discharges (in the most sensitive polarity) were applied to the center of one vertical edge of the Vertical Coupling Plane in sufficiently different positions that the four faces of the EUT were completely illuminated. The VCP (dimensions 0.5m x 0.5m) was placed vertically to and 0.1 meters from the EUT.



4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



NOTE:

TABLE-TOP EQUIPMENT

The configuration consisted of a wooden table 0.8 meters high standing on the **Ground Reference Plane**. The **GRP** consisted of a sheet of aluminum at least 0.25mm thick, and 2.5 meters square connected to the protective grounding system. A **Horizontal Coupling Plane** (1.6m x 0.8m) was placed on the table and attached to the **GRP** by means of a cable with 940kΩ total impedance. The equipment under test, was installed in a representative system as described in section 7 of IEC 61000-4-2, and its cables were placed on the **HCP** and isolated by an insulating support of 0.5mm thickness. A distance of 0.8-meter minimum was provided between the EUT and the walls of the laboratory and any other metallic structure.

FLOOR-STANDING EQUIPMENT

The equipment under test was installed in a representative system as described in section 7 of IEC 61000-4-2, and its cables were isolated from the Ground Reference Plane by an insulating support of 0.1-meter thickness. The GRP consisted of a sheet of aluminum that is at least 0.25mm thick, and 2.5 meters square connected to the protective grounding system and extended at least 0.5 meters from the EUT on all sides.



4.2.6 TEST RESULTS

TEST MODE	See section 2.2	ENVIRONMENTAL CONDITIONS	24.6deg. C, 54.5% RH, 102.0kPa
TESTED BY	Dragon		



Direct Discharge Application				
Test Level (kV)	Polarity	Test Point	Test Result of Contact Discharge	Test Result of Air Discharge
4	+ /-	All metal part	A	N/A
8	+ /-	All non-metal Part	N/A	N/A

Indirect Discharge Application				
Discharge Level (kV)	Polarity	Test Point	Test Result of HCP	Test Result of VCP
4	+ /-	HCP	A	N/A
4	+ /-	VCP	N/A	A

NOTE: A: There was no change compared with initial operation during the test.

ESD TEST POINT

○ - Direct Contact Discharge; ✦ - Air Discharge





4.3 RADIATED, RADIO-FREQUENCY, ELECTROMAGNETIC FIELD IMMUNITY TEST (RS) (EN55035)

4.3.1 TEST SPECIFICATION

Basic Standard:	IEC 61000-4-3
Frequency Range:	80-1000MHz, 1800MHz, 2600MHz, 3500MHz, 5000MHz
Field Strength:	3 V/m
Modulation:	1kHz Sine Wave, 80%, AM Modulation
Frequency Step:	1 % of fundamental
Polarity of Antenna:	Horizontal and Vertical
Antenna Height:	1.5m
Dwell Time:	at least 3 seconds

4.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Signal Generator	Agilent	N5181A	MY50142530	Sep. 12,19	Sep. 11,20
Antenna Log-Periodic	AR	ATR80M6G	0337307	N/A	N/A
Antenna Log-Periodic	AR	ATS700M11G	0336821	N/A	N/A
Switch Controller	AR	SC1000	0337343	N/A	N/A
RF Power Meter	Boonton	4242	13984	Sep. 12,19	Sep. 11,20
Power Sensor	Boonton	51011EMC	35716	Sep. 12,19	Sep. 11,20
Power Sensor	Boonton	51011EMC	35715	Sep. 12,19	Sep. 11,20
E-Field probe	Narda	NBM-520	2403/01B	Dec. 24,19	Dec. 23,20
Power Amplifier	TESEQ	CBA 1G-150	T44029	N/A	N/A
Power Amplifier	TESEQ	CBA 3G-100	T44030	N/A	N/A
Power Amplifier	TESEQ	CBA 6G-050	1041204	N/A	N/A
Dual Directional Coupler	TESEQ	C5982	95208	Sep. 21,19	Sep. 20,20
Dual Directional Coupler	TESEQ	C6187	95175	Sep. 21,19	Sep. 20,20
Dual Directional Coupler	TESEQ	CPH-274F	M251304-01	Sep. 21,19	Sep. 20,20
Audio analyzer	Rohde&Schwarz	UPV	101397	Sep. 18,19	Sep. 17,20
Conditioning Amplifier	B&K	2690A0S2	2437856	Oct. 18,19	Oct. 17,20
EAR SIMULATOR	B&K	4192	2764719	Jun. 01,19	May 30,20
Test Software	Tonscend	TS+	2.0.1.8	N/A	N/A
Test Software	ADT	BVADT_RS_V 7.6.4-DG	N/A	N/A	N/A

NOTE: 1. The test was performed in RS chamber.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



4.3.3 TEST PROCEDURE

The test procedure was in accordance with IEC 61000-4-3

- a. The testing was performed in a fully-anechoic chamber.
- b. The frequency range is swept from 80 MHz to 1000 MHz, 1800MHz, 2600MHz, 3500MHz, 5000MHz, with the signal 80% amplitude modulated with a 1kHz sine wave.
- c. The dwell time at each frequency shall not be less than the time necessary for the EUT to be exercised and to respond, but shall in no case be less than 0,5s.
- d. The field strength levels were 3V/m.
- e. The test was performed with the EUT exposed to both vertically and horizontally polarized fields on each of the four sides.

For Broadcast reception function:

- f. **Group1:** Equipment in which the desired RF broadcast signal enters the equipment through a coaxial broadcast receiver tuner port. These coaxial ports are intended to be connected via a coaxial cable to an antenna or a cable distribution system.
- g. **Group 2:** Broadcast reception equipment which is not included in Group 1.
- h. AM/FM/DAB equipment with a coaxial broadcast receiver tuner port is classified as Group 2 equipment if the manufacturer declares that the equipment is not intended to be connected to a CATV or other cable distribution network.
- i. The broadcast reception function shall be tested in each reception mode for which the receiver is designed, for example analogue reception, DVB-T, DVB-T2, DVB-C, DVB-C2, DVB-S, DVB-S2. The receiver shall be tuned to one channel and provided with an appropriate wanted signal on that channel or other input typical of normal use.


4.3.4 DEVIATION FROM TEST STANDARD

No deviation.




4.3.5 TEST SETUP

For Picture monitoring:




For Acoustic mode:





For Electrical mode:



NOTE:

1. The EUT installed in a representative system as described in section 7 of IEC 61000-4-3 was placed on a non-conductive table 0.8 meters in height. The system under test was connected to the power and signal wire according to relevant installation instructions.
2. Filter: 1kHz 3dB band pass filter.
3. The measurement distance: EUT to interference antenna was 3m.



4.3.6 TEST RESULTS

TEST MODE	See section 2.2	TEST VOLTAGE	See section 2.2
ENVIRONMENTAL CONDITIONS	22.7deg., 57.6% RH	TESTED BY: Dragon	

Field Strength (V/m)	Test Frequency Note (MHz)	Polarization of antenna (Horizontal / Vertical)	Test Distance (m)	Test Result	Remark
3	80-1000MHz, 1800MHz, 2600MHz, 3500MHz, 5000MHz	H&V	3	A	Pass

NOTE: A: There was no change compared with initial operation during the test



4.4 RADIATED, RADIO-FREQUENCY, ELECTROMAGNETIC FIELD IMMUNITY TEST (RS) (EN301489)

4.4.1 TEST SPECIFICATION

Basic Standard:	EN 61000-4-3
Frequency Range:	80 MHz ~ 6000 MHz
Field Strength:	3 V/m
Modulation:	1 kHz Sine Wave, 80%, AM Modulation
Frequency Step:	1% of preceding frequency value
Polarity of Antenna:	Horizontal and Vertical
Antenna Height:	1.5 m
Dwell Time:	3 seconds

4.4.2 TEST INSTRUMENT

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Signal Generator	Agilent	N5181A	MY50142530	Sep. 12,19	Sep. 11,20
Antenna Log-Periodic	AR	ATR80M6G	0337307	N/A	N/A
Antenna Log-Periodic	AR	ATS700M11G	0336821	N/A	N/A
Switch Controller	AR	SC1000	0337343	N/A	N/A
RF Power Meter	ESE	4242	13984	Sep. 12,19	Sep. 11,20
Power Sensor	ESE	51011EMC	35716	Sep. 12,19	Sep. 11,20
Power Sensor	ESE	51011EMC	35715	Sep. 12,19	Sep. 11,20
E-Field probe	Narda	NBM-520	2403/01B	Dec. 24,19	Dec. 23,20
Power Amplifier	TESEQ	CBA 1G-150	T44029	N/A	N/A
Power Amplifier	TESEQ	CBA 3G-100	T44030	N/A	N/A
Power Amplifier	TESEQ	CBA 6G-050	1041204	N/A	N/A
Dual Directional Coupler	TESEQ	C5982	95208	Sep. 21,19	Sep. 20,20
Dual Directional Coupler	TESEQ	C6187	95175	Sep. 21,19	Sep. 20,20
Dual Directional Coupler	TESEQ	CPH-274F	M251304-01	Sep. 21,19	Sep. 20,20
Test Software	ADT	BVADT_RS_V7.6 .4-DG	N/A	N/A	N/A

- NOTE:**
1. The test was performed in RS chamber.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



4.4.3 TEST PROCEDURE


The test procedure was in accordance with EN 61000-4-3.

- a. The testing was performed in a fully-anechoic chamber.
- b. The frequency range is swept from 80 MHz to 6000 MHz with the signal 80% amplitude modulated with a 1 kHz sine wave.
- c. The dwell time at each frequency shall not be less than the time necessary for the EUT to be exercised and to respond, but shall in no case be less than 0.5s.
- d. The field strength level was 3 V/m.
- e. The test was performed with the EUT exposed to both vertically and horizontally polarized fields on each of the four sides.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation.

4.4.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

NOTE:

TABLETOP EQUIPMENT

The EUT installed in a representative system as described in section 7 of EN 61000-4-3 was placed on a non-conductive table 0.8 meters in height. The system under test was connected to the power and signal wire according to relevant installation instructions.



4.4.6 TEST RESULTS

TEST MODE	See section 2.2	TEST VOLTAGE	See section 2.2
ENVIRONMENTAL CONDITIONS	22.7deg., 57.6% RH	TESTED BY: Dragon	

Field Strength (V/m)	Test Frequency Note#1 (MHz)	Polarization of antenna (Horizontal / Vertical)	Test Distance (m)	Test Result	Remark
3	80 - 6000	H / V	3	A	Note 1

Note#1: Tested Israel SII Frequencies 89,100,107,144,163,196,244,315,434,460,600,825,845,880 MHz

Note : A: There was no change compared with initial operation during the test.




5 PHOTOGRAPHS OF THE TEST CONFIGURATION


RADIATED EMISSION TEST (30MHz-1GHz)




RADIATED EMISSION TEST (Above 1GHz)



ESD TEST



RS TEST





**BUREAU
VERITAS**

Test Report No.: CE191231N001

6 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---