



FCC TEST REPORT (PART 22)

Applicant:	Particle Industries, Inc
Address:	126 Post St,4th floor, San Francisco, CA 94108 USA

Manufacturer or Supplier:	Particle Industries, Inc
Address:	126 Post St,4th floor, San Francisco, CA 94108 USA
Product:	E Series 2G/3G Global
Brand Name:	Particle
Model Name:	E310, E314
FCC ID:	XPY1CGM5NNN
Date of tests:	Oct. 17, 2019 ~ Nov. 27, 2019

The tests have been carried out according to the requirements of the following standard:

- FCC PART 22, Subpart H FCC Part 2
- ANSI/TIA/EIA-603-D ANSI C63.26-2015
- ANSI/TIA/EIA-603-E

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Remark: This test report is for internal customer use only, not as a final certification test report.

Prepared by Alex Chen Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
Date: Dec. 23, 2020	Date: Dec. 23, 2020

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELEASE CONTROL RECORD4

1 SUMMARY OF TEST RESULTS.....5

1.1 MEASUREMENT UNCERTAINTY5

1.2 TEST SITE AND INSTRUMENTS6

2 GENERAL INFORMATION7

2.1 GENERAL DESCRIPTION OF EUT7

2.2 CONFIGURATION OF SYSTEM UNDER TEST9

2.3 DESCRIPTION OF SUPPORT UNITS10

2.4 TEST ITEM AND TEST CONFIGURATION.....10

2.5 EUT OPERATING CONDITIONS11

2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS12

3 TEST TYPES AND RESULTS.....13

3.1 OUTPUT POWER MEASUREMENT13

3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT13

3.1.2 TEST PROCEDURES13

3.1.3 TEST SETUP14

3.1.4 TEST RESULTS14

3.2 FREQUENCY STABILITY MEASUREMENT16

3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT16

3.2.2 TEST PROCEDURE16

3.2.3 TEST SETUP16

3.2.4 TEST RESULTS17

3.3 OCCUPIED BANDWIDTH MEASUREMENT19

3.3.1 TEST PROCEDURES19

3.3.2 TEST SETUP19

3.3.3 TEST RESULTS20

3.4 BAND EDGE MEASUREMENT22

3.4.1 LIMITS OF BAND EDGE MEASUREMENT22

3.4.2 TEST SETUP22

3.4.3 TEST PROCEDURES23

3.4.4 TEST RESULTS24

3.5 CONDUCTED SPURIOUS EMISSIONS.....25

3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT25

3.5.2 TEST PROCEDURE25

3.5.3 TEST SETUP25

3.5.4 TEST RESULTS26

3.6 RADIATED EMISSION MEASUREMENT28

3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT28

3.6.2 TEST PROCEDURES28

3.6.3 DEVIATION FROM TEST STANDARD28

3.6.4 TEST SETUP29



**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

3.6.5	TEST RESULTS	30
3.7	PEAK TO AVERAGE RATIO	44
3.7.1	LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT	44
3.7.2	TEST SETUP	44
3.7.3	TEST PROCEDURES	44
3.7.4	TEST RESULTS	45
4	PHOTOGRAPHS OF THE TEST CONFIGURATION	51
5	INFORMATION ON THE TESTING LABORATORIES	52
6	APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	53



BUREAU
VERITAS

Test Report No.: RFP20120027-1

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF191017W003-1	Original release, This test report is for internal customer use only, not as a final certification test report.	Nov. 28, 2019
RFP20120027-1	Based on the original product add one model name. In this report, All test data is copied from the original test report RF191017W003-1.	Dec. 23, 2020



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 22 & Part 2		
STANDARD SECTION	TEST TYPE	RESULT
2.1046 22.913 (a)	Effective Radiated Power	Compliance
2.1055 22.355	Frequency Stability	Compliance
2.1049 22.917 (b)	Occupied Bandwidth	Compliance
22.913 (d)	Peak to average ratio*	Compliance
22.917	Band Edge Measurements	Compliance
2.1051 22.917	Conducted Spurious Emissions	Compliance
2.1053 22.917	Radiated Spurious Emissions	Compliance

* Refer to KDB 971168 D01 Power Meas License Digital Systems v03r01.

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
Maximum Peak Output Power	±2.06dB
Frequency Stability	± 76.97Hz
Radiated emissions (30MHz~1GMHz)	±4.98dB
Radiated emissions (1GMHz ~6GMHz)	±4.70dB
Radiated emissions (6GMHz ~18GMHz)	±4.60dB
Radiated emissions (18GMHz ~40GMHz)	±4.12dB
Conducted emissions	±4.01dB
Occupied Channel Bandwidth	±43.58KHz
Band Edge Measurements	±4.70dB
Peak to average ratio	±0.76dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



1.2 TEST SITE AND INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Feb. 26,19	Feb. 25,20
EXA Signal Analyzer	KEYSIGHT	N9010A-526	MY54510322	Feb. 26,19	Feb. 25,20
Bilog Antenna 1	ETS-LINDGREN	3143B	00161964	Feb. 26,19	Feb. 25,20
Bilog Antenna 2	ETS-LINDGREN	3143B	00161965	Feb. 26,19	Feb. 25,20
Horn Antenna 1	ETS-LINDGREN	3117	00168728	Feb. 26,19	Feb. 25,20
Horn Antenna 2	ETS-LINDGREN	3117	00168692	Nov. 24, 19	Nov. 23, 20
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40 -K-SG/QMS-00 361	15433	Nov. 24, 19	Nov. 23, 20
Radio Communication Analyzer	ANRITSU	MT8820C	6201465426	Feb. 26,19	Feb. 25,20
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jun. 24,19	Jun. 23,20
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jun. 24,19	Jun. 23,20
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Jun. 24,19	Jun. 23,20
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn- CT0001143-1216	Feb. 26,19	Feb. 25,20
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SM A	1505	Jun. 24,19	Jun. 23,20
Power Meter	Anritsu	ML2495A	1506002	Feb. 26,19	Feb. 25,20
Power Sensor	Anritsu	MA2411B	1339352	Feb. 26,19	Feb. 25,20
Humid & Temp Programmable Tester	Juyi	ITH-120-45-CP -AR	IAA1504-001	Jun. 24,19	Jun. 23,20
MXG Analog Microvave Signal Generator	KEYSIGHT	N5183A	MY50143024	Feb. 26,19	Feb. 25,20

NOTE: 1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.

3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.

4. The FCC Site Registration No. is 525120; The Designation No. is CN1171.



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

EUT	E Series 2G/3G Global	
BRAND NAME	Particle	
MODEL NAME	E310, E314	
POWER SUPPLY	DC 5V from Host Uint or DC 3.7V from Li-ion battery Vnor=3.7V,Vmin=3.145V,Vmax=4.255V	
MODULATION TYPE	GSM/GPRS	GMSK
	WCDMA	BPSK, QPSK
FREQUENCY RANGE	GSM/GPRS	824.2MHz ~ 848.8MHz
	WCDMA	826.4MHz ~ 846.6MHz
MAX. ERP POWER	GSM	1334mW
	WCDMA	167mW
EMISSION DESIGNATOR	GSM	244KGXW
	WCDMA	4M08F9W
ANTENNA TYPE	Fixed External Antenna with 1.42dBi gain	
HW VERSION	V005	
SW VERSION	V1.4.0	
I/O PORTS	Refer to user's manual	

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The schematic and PCB of the E314 is completely the same with E310, and these two models of HW&SW is the same. Because changing the MVNO's E-SIM card (embedded SIM card) provider from Kore to Twilio, so we plan to use different model name to sell it in market. The differences are as follows:E310 uses eSIM of Kore.E314 uses eSIM of Twilio.
- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
- The EUT incorporates a SISO function. Physically, the EUT provides one completed transmitter and one receiver.


MODULATION MODE	TX FUNCTION
GSM/GPRS	1TX/1RX
WCDMA	1TX/1RX



Test Report No.: RFP20120027-1



2.2 CONFIGURATION OF SYSTEM UNDER TEST FOR RADIATION EMISSION





2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Battery	N/A	N/A	N/A	N/A
2	DC source	LONG WEI	PS-6403D	010934269	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A
2	DC Line: Unshielded, Detachable 1.0m

2.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case in radiated emission was found when positioned on X-plane for GSM/GPRS /WCDMA. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
	EUT + Battery with GSM or WCDMA link

GSM MODE

TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
ERP	128 to 251	128, 189, 251	GSM
FREQUENCY STABILITY	128 to 251	128, 251	GSM
OCCUPIED BANDWIDTH	128 to 251	128, 189, 251	GSM
BAND EDGE	128 to 251	128, 251	GSM
CONDCUDED EMISSION	128 to 251	128, 189, 251	GSM
RADIATED EMISSION	128 to 251	128, 189, 251	GSM
PEAK TO AVERAGE RATIO	128 to 251	128, 189, 251	GSM



WCDMA MODE

TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
ERP	4132 to 4233	4132, 4182, 4233	WCDMA
FREQUENCY STABILITY	4132 to 4233	4132, 4233	WCDMA
OCCUPIED BANDWIDTH	4132 to 4233	4132, 4182, 4233	WCDMA
BAND EDGE	4132 to 4233	4132, 4233	WCDMA
CONDCUDED EMISSION	4132 to 4233	4132, 4182, 4233	WCDMA
RADIATED EMISSION	4132 to 4233	4132, 4182, 4233	WCDMA
PEAK TO AVERAGE RATIO	4132 to 4233	4132, 4182, 4233	WCDMA

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
ERP	23deg. C, 70%RH	DC 3.7V by battery	Star Le
FREQUENCY STABILITY	23deg. C, 70%RH	DC 3.7V/3.145/4.255 by DC source	Big Wang
OCCUPIED BANDWIDTH	23deg. C, 70%RH	DC 3.7V by battery	Big Wang
BAND EDGE	23deg. C, 70%RH	DC 3.7V by battery	Big Wang
CONDCUDED EMISSION	23deg. C, 70%RH	DC 3.7V by battery	Big Wang
RADIATED EMISSION	23deg. C, 70%RH	DC 3.7V by battery	Star Le
PEAK TO AVERAGE RATIO	23deg. C, 70%RH	DC 3.7V by battery	Big Wang

2.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency



Test Report No.: RFP20120027-1

2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 22

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-D

ANSI/TIA/EIA-603-E

ANSI C63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.

3 TEST TYPES AND RESULTS

3.1 OUTPUT POWER MEASUREMENT

3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile / Portable station are limited to 7 watts e.r.p.

3.1.2 TEST PROCEDURES

EIRP / ERP MEASUREMENT:

Per KDB 971168 D01 Power Meas License Digital Systems v03r01 or subclause 5.2.5.5 of ANSI C63.26-2015, the relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_{\text{T}} - L_{\text{C}}$$

Where:

ERP or EIRP = effective radiated power or equivalent isotropically radiated power, respectively

(expressed in the same units as P_{Meas} , typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

G_{T} = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

L_{C} = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

$$\text{ERP} = \text{EIRP} - 2.15$$

CONDUCTED POWER MEASUREMENT:

The EUT was set up for the maximum power with WCDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.



3.1.3 TEST SETUP

CONDUCTED POWER MEASUREMENT:



3.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm)

Band	GSM850		
Channel	128	189	251
Frequency(MHz)	824.2	836.4	848.8
GSM (GMSK, 1Tx-slot)	31.93	31.98	31.89
GPRS (GMSK, 1Tx-slot)	31.89	31.93	31.82
GPRS (GMSK, 2Tx-slot)	31.85	31.88	31.82
GPRS (GMSK, 3Tx-slot)	31.10	31.09	31.03
GPRS (GMSK, 4Tx-slot)	29.94	29.97	29.91

Band	WCDMA V		
Channel	4132	4182	4233
Rx Channel	4357	4407	4458
Frequency (MHz)	826.4	836.4	846.6
RMC 12.2K	22.95	22.81	22.77
HSDPA Subtest-1	22.03	21.96	21.82
HSDPA Subtest-2	21.99	21.89	21.69
HSDPA Subtest-3	21.51	21.48	21.36
HSDPA Subtest-4	21.48	21.52	21.33
HSUPA Subtest-1	21.98	21.86	21.82
HSUPA Subtest-2	20.01	19.95	19.79
HSUPA Subtest-3	21.04	20.89	20.86
HSUPA Subtest-4	19.95	19.89	19.85
HSUPA Subtest-5	20.93	21.84	21.68



BUREAU
VERITAS

Test Report No.: RFP20120027-1

ERP POWER (dBm)

GSM

Channel	Frequency (MHz)	Conducted Power (dBm)	G_{T-Lc} (dB)	ERP (dBm)	ERP (mW)	Limit (W)
128	824.2	31.93	1.42	31.20	1318.26	7
189	836.4	31.98	1.42	31.25	1333.52	7
251	848.8	31.89	1.42	31.16	1306.17	7

WCDMA

Channel	Frequency (MHz)	Conducted Power (dBm)	G_{T-Lc} (dB)	ERP (dBm)	ERP (mW)	Limit (W)
4132	826.4	22.95	1.42	22.22	166.72	7
4182	836.4	22.81	1.42	22.08	161.44	7
4233	846.6	22.77	1.42	22.04	159.96	7

3.2 FREQUENCY STABILITY MEASUREMENT

3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


1.5 ppm is for base and fixed station. 2.5 ppm is for mobile station.

3.2.2 TEST PROCEDURE

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

3.2.3 TEST SETUP





3.2.4 TEST RESULTS

GSM 850

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
V_{nor}	0.0023	0.0026	2.5
V_{min}	-0.0026	-0.0026	2.5
V_{max}	0.0021	0.0022	2.5

NOTE: The applicant defined the normal working voltage of the battery is from V_{min} to V_{max} .

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
-30	-0.0123	-0.0117	2.5
-20	-0.0116	-0.0110	2.5
-10	-0.0100	-0.0094	2.5
0	-0.0087	-0.0081	2.5
10	-0.0071	-0.0065	2.5
20	-0.0055	-0.0050	2.5
30	-0.0041	-0.0035	2.5
40	-0.0028	-0.0023	2.5
50	-0.0012	-0.0007	2.5



WCDMA Band V

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
V_{nor}	0.0021	0.0024	2.5
V_{min}	-0.0025	-0.0021	2.5
V_{max}	0.0026	0.0026	2.5

NOTE: The applicant defined the normal working voltage of the battery is from V_{min} to V_{max} .

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
-30	-0.0116	-0.0114	2.5
-20	-0.0100	-0.0107	2.5
-10	-0.0085	-0.0083	2.5
0	-0.0077	-0.0072	2.5
10	-0.0047	-0.0054	2.5
20	-0.0043	-0.0041	2.5
30	-0.0038	-0.0041	2.5
40	-0.0019	-0.0016	2.5
50	-0.0003	-0.0006	2.5




3.3 OCCUPIED BANDWIDTH MEASUREMENT

3.3.1 TEST PROCEDURES

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

3.3.2 TEST SETUP






3.3.3 TEST RESULTS

GSM850

CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (kHz)	CHANNEL	Frequency (MHz)	26dB Bandwidth (MHz)
		GSM			GSM
128	824.2	244	128	824.2	316.893
189	836.4	243	189	836.4	318.666
251	848.8	242	251	848.8	319.836






**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

WCDMA V

CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (kHz)	CHANNEL	Frequency (MHz)	26dB Bandwidth (MHz)
		WCDMA V			WCDMA V
4132	826.4	4.080	4132	826.4	4.656
4182	836.4	4.070	4182	836.4	4.647
4233	846.6	4.070	4233	846.6	4.646




3.4 BAND EDGE MEASUREMENT

3.4.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

3.4.2 TEST SETUP





**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

3.4.3 TEST PROCEDURES


- a. All measurements were done at low and high operational frequency range.
- b. The center frequency of spectrum is the band edge frequency and span is 1.5MHz. RBW of the spectrum is 10kHz and VBW of the spectrum is 30kHz (GSM/GPRS).
- c. The center frequency of spectrum is the band edge frequency and span is 10MHz. RBW of the spectrum is 100kHz and VBW of the spectrum is 300kHz (WCDMA).
- d. Record the max trace plot into the test report.



BUREAU VERITAS

Test Report No.: RFP20120027-1

3.4.4 TEST RESULTS



3.5 CONDUCTED SPURIOUS EMISSIONS


3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

3.5.2 TEST PROCEDURE

- a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- b. Measuring frequency range is from 9 kHz to 9GHz. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

3.5.3 TEST SETUP






BUREAU VERITAS

Test Report No.: RFP20120027-1


3.5.4 TEST RESULTS





BUREAU VERITAS

Test Report No.: RFP20120027-1



3.6 RADIATED EMISSION MEASUREMENT

3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

3.6.2 TEST PROCEDURES

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- c. $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $\text{E.R.P power} = \text{E.I.P.R power} - 2.15\text{dBi}$.

NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.


3.6.3 DEVIATION FROM TEST STANDARD

No deviation




3.6.4 TEST SETUP

< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).



3.6.5 TEST RESULTS


BELOW 1GHz WORST-CASE DATA

30 MHz – 1GHz data:

WCDMA Band V:

MODE	TX channel 4182	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 3.7V by battery
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase	
	MHz	dBm/m	dBm	dBm/m	dB	dB/m			
1	PP	31.940	-33.92	-50.59	-13.00	-20.92	16.67	Peak	Horizontal
2		39.700	-42.86	-54.94	-13.00	-29.86	12.08	Peak	Horizontal
3		47.460	-45.86	-51.30	-13.00	-32.86	5.44	Peak	Horizontal
4		84.320	-48.06	-39.81	-13.00	-35.06	-8.25	Peak	Horizontal
5		105.660	-52.10	-39.77	-13.00	-39.10	-12.33	Peak	Horizontal
6		130.880	-56.50	-39.95	-13.00	-43.50	-16.55	Peak	Horizontal






**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

MODE	TX channel 4182	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 3.7V by battery
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	32.910	-39.36	-40.82	-13.00	-26.36	1.46 Peak	Vertical
2		49.400	-44.42	-39.89	-13.00	-31.42	-4.53 Peak	Vertical
3		85.290	-47.01	-36.61	-13.00	-34.01	-10.40 Peak	Vertical
4		106.630	-48.69	-37.14	-13.00	-35.69	-11.55 Peak	Vertical
5		270.560	-66.01	-54.58	-13.00	-53.01	-11.43 Peak	Vertical
6		308.390	-67.76	-56.50	-13.00	-54.76	-11.26 Peak	Vertical





**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

ABOVE 1GHz DATA


Note: For higher frequency, the emission is too low to be detected.

GSM 850

CH 128:

MODE	TX channel 128	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 3.7V by battery
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1648,000	-53,84	-57,09	-13,00	-40,84	3,25	Peak	Horizontal
2 PP	2472,600	-49,85	-57,87	-13,00	-36,85	8,02	Peak	Horizontal






**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

MODE	TX channel 128	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 3.7V by battery
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1648,000	-53,64	-57,02	-13,00	-40,64	3,38	Peak	Vertical
2 PP	2472,600	-50,90	-57,94	-13,00	-37,90	7,04	Peak	Vertical






**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

CH 189:

MODE	TX channel 189	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 3.7V by battery
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1666,000	-54,04	-57,51	-13,00	-41,04	3,47	Peak	Horizontal
2 PP	2509,200	-50,17	-58,23	-13,00	-37,17	8,06	Peak	Horizontal






**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

MODE	TX channel 189	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 3.7V by battery
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1666,000	-52,86	-56,40	-13,00	-39,86	3,54	Peak	Vertical
2 PP	2509,200	-50,41	-57,51	-13,00	-37,41	7,10	Peak	Vertical






**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

CH 251:

MODE	TX channel 251	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 3.7V by battery
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1702,000	-52,29	-56,20	-13,00	-39,29	3,91	Peak	Horizontal
2 PP	2546,400	-50,32	-58,43	-13,00	-37,32	8,11	Peak	Horizontal






**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

MODE	TX channel 251	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 3.7V by battery
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1702,000	-52,75	-56,62	-13,00	-39,75	3,87	Peak	Vertical
2	PP 2546,400	-50,40	-57,62	-13,00	-37,40	7,22	Peak	Vertical





**BUREAU
VERITAS**


Test Report No.: RFP20120027-1

WCDMA Band V:

CH 4132:

MODE	TX channel 4132	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 3.7V by battery
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1648,000	-52,43	-55,68	-13,00	-39,43	3,25	Peak	Horizontal
2	PP 2472,000	-49,39	-57,41	-13,00	-36,39	8,02	Peak	Horizontal






Test Report No.: RFP20120027-1

MODE	TX channel 4132	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 3.7V by battery
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1648,000	-51,76	-55,14	-13,00	-38,76	3,38	Peak	Vertical
2 PP	2472,000	-49,28	-56,32	-13,00	-36,28	7,04	Peak	Vertical






**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

CH 4182:

MODE	TX channel 4182	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 3.7V by battery
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1666,000	-51,16	-54,63	-13,00	-38,16	3,47	Peak	Horizontal
2	PP 2512,000	-49,36	-57,42	-13,00	-36,36	8,06	Peak	Horizontal






**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

MODE	TX channel 4182	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 3.7V by battery
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1666,000	-51,77	-55,31	-13,00	-38,77	3,54	Peak	Vertical
2 PP	2512,000	-50,15	-57,26	-13,00	-37,15	7,11	Peak	Vertical






**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

CH 4233:

MODE	TX channel 4233	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 3.7V by battery
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1702,000	-50,27	-54,18	-13,00	-37,27	3,91	Peak	Horizontal
2 PP	2548,000	-48,21	-56,32	-13,00	-35,21	8,11	Peak	Horizontal






**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

MODE	TX channel 4233	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 3.7V by battery
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1702,000	-51,28	-55,15	-13,00	-38,28	3,87	Peak	Vertical
2	PP 2548,000	-50,20	-57,42	-13,00	-37,20	7,22	Peak	Vertical




3.7 PEAK TO AVERAGE RATIO

3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

3.7.2 TEST SETUP



3.7.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.




**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

3.7.4 TEST RESULTS

GSM

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
128	824.2	2.75






**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
189	836.4	2.77






**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
251	848.8	2.74






**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

WCDMA

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
4132	826.4	2.71






**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
4182	836.4	2.68






**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
4233	846.6	2.71





BUREAU
VERITAS

Test Report No.: RFP20120027-1

4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: RFP20120027-1

5 INFORMATION ON THE TESTING LABORATORIES

We, BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO. LTD., were founded in 2015 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Shenzhen EMC/RF Lab:

Tel: +86-755-88696566

Fax: +86-755-88696577

Email: customerservice.dg@cn.bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



**BUREAU
VERITAS**

Test Report No.: RFP20120027-1

6 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---